



Optimax HF Type 075, Type 150													
L _i (mm) \ b/w (mm)	€/Stück each												
	10	15	20	25	30	35	40	50	60	70	80	90	100
400-600	12,50	15,30	17,90	20,70	23,60	26,20	28,90	36,20	43,40	51,20	57,00	63,70	70,00
601-700	13,50	16,30	19,50	21,40	25,40	28,40	31,50	39,20	46,90	55,40	61,50	68,80	75,70
701-800	14,00	17,80	20,70	23,60	27,00	30,10	33,00	41,40	49,80	58,90	65,00	73,00	80,30
801-900	14,90	18,50	21,90	24,90	28,50	31,80	35,30	44,10	52,70	62,50	69,40	77,70	85,30
901-1000	16,00	19,60	23,20	27,00	30,30	33,90	37,50	46,90	55,90	66,10	73,10	82,10	90,30
1001-1200	17,90	21,90	25,90	29,90	33,40	37,90	41,40	52,20	62,50	73,90	82,00	92,00	101,10
1201-1400	19,70	24,20	28,70	32,80	37,30	41,40	45,80	57,40	68,60	81,10	89,90	101,10	110,70
1401-1600	21,40	26,20	30,70	35,90	40,70	45,30	50,30	63,00	75,50	89,10	99,00	110,70	121,70
1601-1800	23,20	28,50	33,40	38,80	43,60	49,40	54,60	67,70	80,90	95,60	106,20	119,50	131,50
1801-2000	24,90	30,40	36,20	42,00	48,80	52,90	58,90	73,10	87,60	103,60	115,10	128,30	140,30
2001-2200	27,00	32,80	38,80	44,90	51,00	55,90	62,70	78,70	94,50	110,70	123,90	138,10	152,40
2201-2400	28,70	34,90	41,30	47,90	54,50	60,80	67,00	84,00	101,10	119,50	132,60	146,90	163,30
2401-2600	30,30	37,40	43,80	50,60	57,70	64,60	71,40	89,40	107,30	126,10	139,20	156,80	172,10
2601-2800	32,30	39,00	46,90	53,90	61,10	68,50	75,60	94,50	114,00	133,70	148,00	165,50	183,10
2801-3000	33,90	41,40	49,50	57,00	64,60	72,50	80,00	95,60	115,10	135,90	150,20	166,60	184,20
3001-3200	35,90	43,70	52,10	60,00	68,40	76,00	83,90	105,40	125,00	150,20	164,40	184,20	202,80
3201-3400	37,50	46,00	54,70	62,70	71,50	80,00	88,60	109,60	132,60	156,80	172,10	194,00	211,60
3401-3600	38,80	48,40	57,30	65,80	75,10	83,70	92,70	116,20	139,20	164,40	182,00	202,80	224,70
3601-3700	40,40	50,40	59,50	68,40	77,80	87,00	96,30	121,70	142,50	169,90	188,50	211,60	233,50

Type 150: ab Lager lieferbar *delivery ex stock*; Type 075: keine Lagerware *non stock items*

Standard-Sortiment <i>Standard range</i> Optimax HF Type 150 (L _i mm)														
400	550	695	840	980	1130	1280	1430	1580	1740	1890	2070	2280	2550	3150
410	560	700	850	990	1140	1290	1440	1590	1750	1900	2090	2290	2570	3200
420	570	710	860	1000	1150	1300	1450	1600	1760	1920	2100	2300	2600	3250
430	580	720	870	1010	1160	1310	1460	1610	1770	1930	2110	2320	2650	3300
440	590	730	880	1020	1170	1320	1470	1620	1780	1940	2120	2340	2660	3400
450	600	740	890	1030	1180	1330	1480	1630	1790	1950	2130	2350	2700	3500
460	610	750	900	1040	1190	1340	1490	1640	1800	1960	2140	2370	2750	3600
470	620	760	910	1050	1200	1350	1500	1650	1810	1970	2150	2380	2780	
480	630	770	920	1060	1210	1360	1510	1660	1820	1980	2190	2400	2800	
490	640	780	930	1070	1220	1370	1520	1670	1830	2000	2200	2430	2850	
500	650	790	935	1080	1230	1380	1530	1680	1840	2020	2210	2440	2900	
510	660	800	940	1090	1240	1390	1540	1700	1850	2030	2220	2450	2950	
520	670	810	950	1100	1250	1400	1550	1710	1860	2040	2240	2480	3000	
530	680	820	960	1110	1260	1410	1560	1720	1870	2050	2250	2500	3050	
540	690	830	970	1120	1270	1420	1570	1730	1880	2060	2270	2520	3100	

<p>Breiten Dieses Standard-Sortiment kann in jeder beliebigen Breite bis max. 420 mm geliefert werden.</p> <p>Zwischenlängen Außer diesen Standardlängen kann auf Anfrage jede Länge zwischen 200 und 3700 mm geliefert werden.</p> <p>Weitere Qualitäten und Sonderausführungen auf Anfrage.</p>	<p>Aufpreis für Mindermengen Type 150: 1 bis 5 Stück = 25 %</p> <p>Mindest-Abnahmemenge Type 075: 1 Wickel = 330 mm ± 10 %</p> <p>Toleranzen a) Längentoleranz: ± 1 %, mindestens ± 3 mm b) Breitentoleranz: ± 0,5 mm, bis auf ± 0,2 mm reduzierbar</p> <p>Gewicht Type 075 ≈ 0,620 kg/m² Type 150 ≈ 1,210 kg/m²</p>	<p>Widths Above length range can be supplied in every width up to max. 420 mm.</p> <p>Intermediate lengths As well as standard lengths, intermediate lengths between 200 and 3700 mm can be supplied on request.</p> <p>Further qualities and special constructions on request.</p>	<p>Minimum order quantity surcharge Type 150: 1 up to 5 pieces = 25 %</p> <p>Minimum order quantity Type 075: 1 sleeve = 330 mm ± 10 %</p> <p>Tolerances a) Length tolerance: ± 1 %, minimum ± 3 mm b) Width tolerance: ± 0.5 mm, reducible down to ± 0.2 mm</p> <p>Weight Type 075 ≈ 0.620 kg/m² Type 150 ≈ 1.210 kg/m²</p>
--	--	--	--